



# TYPE APPROVAL CERTIFICATE

Certificate no.:  
**TAK00001VT**  
Revision No:  
**1**

**This is to certify:**  
**that the Polyester Resins**

with type designation(s)  
**ESTROMAL DL.115 Series**

issued to  
**LERG S.A.**  
**Pustkow, Poland**

is found to comply with  
**DNV class programme DNV-CP-0083 – Type approval – Polyester resin, vinylester resin, gelcoat and topcoat**  
**DNV rules for classification – High speed and light craft**  
**DNV standard DNV-ST-0342 – Craft**

## Application:

**Grade 2 polyester resin for use in marine vessels in accordance with stated Rules/Standards.**

**Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.**

Issued at **Hamburg** on **2025-05-07**

This Certificate is valid until **2030-05-28**.

for **DNV**

DNV local unit: **Katowice CMC**

Approval Engineer: **Gisle Hersvik**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

## Product description

**ESTROMAL DL.115 Series:** Unsaturated DCPD-based Polyester Resin

### Non-LSE variants

ESTROMAL DL.115-XXXXXXX

### LSE variants

ESTROMAL DL.115-XXXXXXX LSE

### Base

ESTROMAL 11.DC - 11 BASE.

The following properties have been established by type testing of cured base resin.

Property	Test Method	Value *	
Tensile strength	ISO 527-1,2	56,7	MPa
Tensile modulus	ISO 527-1,2	3408	MPa
Elongation at break	ISO 527-1,2	1,71	%
Density	ISO 1183-1	1,191	g/cm <sup>3</sup>
Barcol hardness	EN 59	47	-
Water absorption	ISO 62	78,1	mg
HDT	ISO 75, Method A	66,1	°C
* mean values			

## Application/Limitation

For use in construction of FRP laminates of components, on condition that fibre reinforcement comply with the applicable requirements of DNV and are compatible with the resin.

Any significant changes in design and / or quality of the material will render the approval invalid.

## Type Approval documentation

### Tests carried out

Type Testing carried out in accordance with **Type Approval documentation**.

### Marking of product

Product/package shall be marked with *manufacturer's name: **LERG S.A.**, place of production, type designation, batch number, production date, net weight, gross weight and shelf life.*

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV Type Approval Certificate.

### Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention / Certificate Renewal) shall be performed according to DNV-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

END OF CERTIFICATE